

Internal thread repair kit IGRW-1007

Specifications

- **Everything in one suitcase:** tools for repairing internal threads
- **Diameter range:** M8 – M20 ($\frac{5}{16}$ " – $\frac{13}{16}$ ")
- No Calibration required
- Self adjusting to any pitch and size within range
- Automatically chases good thread sections to repair the damaged parts
- Hardened cutting blades (HSS)
- Removes rust and burrs



	ØD Range	Pipes	L	B	H	ROD	Ør	ØR	Package Size		Weight	
									W	H	lb	gm
i21 inch	$\frac{5}{16} - \frac{7}{16}$	$\frac{1}{16} - \frac{3}{16}$	$4 \frac{5}{16}$	$\frac{11}{16}$	$1 \frac{3}{4}$	$4 \frac{9}{16}$	$\frac{20}{32}$	$1 \frac{17}{32}$	$4 \frac{1}{2}$	$7 \frac{3}{8}$	0.32	160
i21 mm	8 - 11		109	18	45	116	16	38	115	187		
i22 inch	$\frac{1}{2} - \frac{5}{8}$	$\frac{1}{4} - \frac{3}{8}$	$4 \frac{5}{16}$	$\frac{11}{16}$	$1 \frac{3}{4}$	$4 \frac{9}{16}$	$\frac{11}{16}$	$1 \frac{9}{16}$	$4 \frac{1}{2}$	$7 \frac{3}{8}$	0.37	170
i22 mm	12 - 16		109	18	45	116	17	39	115	187		
i23 inch	$\frac{11}{16} - \frac{13}{16}$	$\frac{3}{8} - \frac{1}{2}$	$4 \frac{3}{8}$	$\frac{13}{16}$	$2 \frac{1}{16}$	$5 \frac{1}{8}$	$\frac{13}{16}$	$1 \frac{3}{4}$	$4 \frac{1}{2}$	$7 \frac{3}{8}$	0.55	250
i23 mm	16 - 20		111	21	53	130	20	45	115	187		

